

Nasiff CardioCard[®]

CARDIOCARD MOBILE™ ECG SYSTEM

Ultra Portable
Convenient
Affordable

Use the Latest Technology

Unlimited Database

EMR
Connectivity
Built-in Networking
Simple

For WINDOWS, Android™ phones and tablets. MACs, iPhones and iPads



(mobile devices and laptop sold separately)



CardioCard Mobile™ ECG — we care about you and your patients

Nasiff Associates, Inc. is the **FIRST** and continues to take the lead in PC-Based Resting ECG Systems. A true 12-lead interpretive ECG. We are now available in the **MOBILE DEVICE** market performing fast testing and managing them easily with you at the point-of-care.

- Performs ECG's on mobile devices
(Android™ cell phones and tablets. Apple iPhone and iPad...)
- Cardio Universal EMR Interface™
- Cardio Patient Data Management™ System
- Built-In Networking
- Unlimited Patient Database
- Legendary quality, excellent customer support and training
- Reliable, user-friendly, compact and durable devices
- Feature rich at the best price
- Made in USA
- FDA Clearance since 1989



Nasiff CardioCard[®]

CARDIOCARD MOBILE™ ECG SYSTEM

SPECIFICATIONS



DATA ACCESS	Store and save in CardioCard [®] database
POWER SUPPLY	DC 3v from two AA batteries
FORMATS	Save to pdf and email anywhere directly from device
CONNECTION WITH MOBILE DEVICES	Bluetooth [®] for Android, Windows and MAC. WiFi for iPhone and iPad
POWER CONSUMPTION	< 200mA at 5V from PC Bus
ECG MEASUREMENT RESOLUTIONS	2-4 msec, 1.22uV at 10mm/mV gain
HEART RATE RANGE	30-300bpm
LEADS	Standard 12- lead
LEAD LEAKAGE	< 10uA
ACQUISITION MODE	Simultaneous interpretive 12- lead acquisition
SAMPLING RATE	12- lead sampling rate 250-1000Hz
A/D RATE	1kHz
TIME BASE	12.5, 25 and 50 mm/sec
DYNAMIC RANGE	± 5 mV
FREQUENCY RESPONSE	0.05 to 150 Hz (<i>higher available</i>)
GAINS	2.5, 5, 10, 10/5, 20, 40 mm/mV
INPUT IMPEDANCE	>10 ¹² ohms
SYSTEM NOISE	<40 mV RTI
ECG INTERPRETATION CLASSES¹	MIs, blocks, enlargements, axis and AFib
FILTERS¹	High performance baseline filter Baseline correction and other filters to minimize motion artifact
CMRR	>120 dB
NETWORKING	Built-in
MEASUREMENTS	HR with global measurements, complete interval values and ST information
DIMENSIONS	2.75" W x 1.25" D x 4.87" H (6.985 cm x 3.175 cm x 12.364 cm)
WEIGHT	0.26 lb (0.12 kg)
PC REQUIREMENTS	Tablet/Laptop/Desktop PC, Intel Compatible, 512MB RAM, 40GB HD, WINDOWS XP through WINDOWS 7, 8, 10 and MAC's with Boot Camp, Dual Boot, VMware Fusion or Parallels
WARRANTY	2-year limited warranty, support and training

Note 1: performed remotely

ORDERING INFORMATION CardioMobile System — CC-ECG1 BTM
 FOR MORE INFORMATION CONTACT: CC-ECG1 WM

Nasiff Associates, Inc. 841-1 County Route 37, Central Square, NY 13036
 phone: 315.676.2346 • fax: 315.676.4711 • toll-free: 866.NASIFFA (866.627.4332)
 tech support: 315.676.2346 • email: sales@nasiff.com • web: www.nasiff.com

CPT CODE 93000 (additional codes: 93005; 93010)



USA FDA Clearance since 1989

Veteran Owned
 Made in USA

